

PATENT  
Attorney Docket Number V637-02674

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

APPLICATION FOR UNITED STATES PATENT

**VERTICAL CAVITY SURFACE EMITTING LASER INCLUDING INDIUM  
AND NITROGEN IN THE ACTIVE REGION**

INVENTOR

Ralph Johnson

211 Ridgeview

Murphy, TX 75094

A Citizen of the United States of America

**EXPRESS MAIL NO.: EL597435837US**

**VERTICAL CAVITY SURFACE EMITTING LASER INCLUDING INDIUM  
AND NITROGEN IN THE ACTIVE REGION**

5

**TECHNICAL FIELD**

This invention relates to vertical cavity surface emitting lasers and more particularly to vertical cavity surface emitting lasers utilizing a combination of nitrogen, aluminum, antimony, phosphorous and/or indium as a material system and as a means to increase VCSEL device wavelength.

10

## BACKGROUND OF THE INVENTION

Solid-state semiconductor lasers are important devices in applications such as optoelectronic communication systems and high-speed printing systems. Recently, there has been an increased interest in vertical cavity surface emitting lasers ("VCSELs") although edge emitting lasers are currently used in the vast majority of applications. A reason for the interest in VCSELs is that edge emitting lasers produce a beam with a large angular divergence, making efficient collection of the emitted beam more difficult. Furthermore, edge emitting lasers cannot be tested until the wafer is cleaved into individual devices, the edges of which form the mirror facets of each device. On the other hand, not only does the beam of a VCSEL have a small angular divergence, a VCSEL emits light normal to the surface of the wafer. In addition, since VCSELs incorporate the mirrors monolithically in their design, they allow for on-wafer testing and the fabrication of one-dimensional or two-dimensional laser arrays.

VCSELs are typically made by growing several layers on a substrate material. VCSELs include a first mirrored stack, formed on the substrate by semiconductor manufacturing techniques, an active region, formed on top of the first mirrored stack, and a second mirrored stack formed on top of the active region. By providing a first contact on top of the second mirrored stack, and a second contact on the backside of the substrate, a current is forced through the active region, thus driving the VCSEL.

The active region is made up further of one or more quantum wells sandwiched between two spacer cladding regions. Inside the spacers, the active region is sandwiched by confining layers. The confining layers or regions are used to provide electrical confinement of minority carriers. By selecting the appropriate materials for the quantum well, the confining layers, and the barrier layers, a VCSEL generally may be grown or fabricated that generates light at a

desirable, predetermined wavelength. For example, by using InGaAs quantum wells on GaAs substrates longer wavelength VCSELs can be produced. The use of InGaAs quantum wells, however, causes strain in the quantum wells. If the quantum wells are grown past their critical thickness, they relax by creating  
5 dislocations, and thus a poor quality active region.

The thickness of the various layers in the active region while not arbitrary have some flexibility within the constraints of the design and the process. The combined thickness of the spacers, the confining layers, the barriers and the  
10 active regions sandwiched by the mirrors must be such that a Fabry Perot resonator is formed. The quantum wells should be positioned so that they are roughly centered at an antinode of the electric field. These two requirements define the spacer thickness in terms of the other layer thicknesses. The barrier layer thicknesses between the quantum wells need to be thick enough to  
15 adequately define the quantum wells, but thin enough that the quantum well positions are not excessively far from the antinode of the electric field. The thickness of the barrier layers at the boundaries of the quantum well regions have some flexibility. Optimally they need to be at least thick enough that the energy levels of each of the quantum wells is nominally the same. They can be  
20 thicker if material quality issues require this. The confining layers are often one in the same with the spacers or, as is shown in this work, can grade stepwise or continuously in the valence and conduction bands towards that of the barriers. Sometimes the confining layers and barrier layers are made from the same compositions, but this is not optimal for carrier confinement and is usually a  
25 compromise made for processing reasons.

The thickness of the quantum well is related by quantum mechanics to the well and barrier compositions, the desired emission wavelength, and the density of states. With a higher density of states narrower quantum wells can be  
30 optimally used.

What is needed in the VCSEL art are means to achieve long wavelength quantum wells normally fabricated on GaAs substrates. The present inventor has recognized that it would be advantageous to remedy the foregoing and other deficiencies in the prior art, and to facilitate the easier production of longer wavelength VCSELs. Accordingly, the present invention is described and presented as a novel methods and means to address the shortcomings currently found in the art.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2

## SUMMARY OF THE INVENTION

The following summary of the invention is provided to facilitate an understanding of some of the innovative features unique to the present invention, and is not intended to be a full description. A full appreciation of the various aspects of the invention can be gained by taking the entire specification, claims, drawings, and abstract as a whole. Additional objects and advantages of the current invention will become apparent to one of ordinary skill in the art upon reading the specification.

In accordance with addressing the limitations of the prior art, presented are new and improved features applied to the solid state laser art that are capable of providing longer wavelength VCSEL devices.

It is a feature of the present invention to provide a method of fabricating improved VCSELs.

In accordance with various aspects of the present invention, quantum wells and/or associated barrier layers can be grown with several novel combinations of nitrogen, aluminum, antimony, phosphorous and/or indium placed within or about a typical GaAs substrate to achieve long wavelength VCSEL performance, e.g., within the 1260 to 1650 nm range useful for fiberoptic communication.

In accordance with a feature of the present invention, a VCSEL is provided wherein InGaAs with N is introduced in the quantum well(s) with confining regions comprised of AlGaAs.

In accordance with another feature of the present invention, a VCSEL is provided wherein InGaAs with N is introduced in the quantum well(s) and the barrier layers.

5 In accordance with another feature of the present invention, a VCSEL is provided wherein InGaAs with N is introduced in the quantum well(s) and barrier layers and aluminum is added to the confining layers.

10 In accordance with another feature of the present invention, a VCSEL is provided wherein InGaAs with N is introduced in the quantum well(s) and Al is introduced in the barrier and confining layers.

15 In accordance with another feature of the present invention, a VCSEL is provided wherein InGaAs with Sb and >1% N is added to the quantum well(s).

In accordance with another feature of the present invention, a VCSEL is provided wherein InGaAsN and Sb are introduced in the quantum well(s) and GaAsN is introduced in the barrier layers.

20 In accordance with another feature of the present invention, a VCSEL is provided wherein an InGaAsSbN quantum well is provided with GaAsP barrier layers and AlGaAs confinement layers.

25 In accordance with another feature of the present invention, a VCSEL is provided wherein InGaAs is provided in the quantum well(s) (no N) with GaAsN barrier layers and AlGaAs confining regions.

30 In accordance with another feature of the present invention, a VCSEL is provided wherein AlGaAs barrier layers are provided with at least one GaAs quantum well including N, Sb and/or In introduced in the quantum well(s).

In accordance with another aspect of the present invention, Nitrogen can be added to the barrier layers of the InGaAs quantum wells of a VCSEL such that the barrier layers are in tension while the quantum wells are in compression. To compensate for the property changes inherent with the addition of Nitrogen to InGaAs quantum wells, quantum well thickness can be reduced. Nitrogen can be useful for strain compensation and overall band gap reduction within the active region.

In accordance with another feature of the present invention, AlGaAs or AlGaAsN can be used for minority carrier confinement in the barrier layers to avoid type 2 behavior in the valence band.

In accordance with another feature of the present invention, Nitrogen or nitrogen and Sb can be used in GaAs or InGaAs quantum wells. The Sb and nitrogen are balanced to avoid a type 2 transition in either the valence band or the conduction band and maintain excellent carrier confinement with at least a 0.1 eV band discontinuity of both the valence and conduction bands at the quantum well edge.

In accordance with features of the present invention, a vertical cavity surface emitting laser (VCSEL) can include at least one quantum well comprised of InGaAsN; barrier layers sandwiching said at least one quantum well; and confinement layers sandwiching said barrier layers. Confinement and barrier layers can comprise AlGaAs, GaAsN. Barrier layers can also comprise InGaAsN. Quantum wells can also include Sb.

Quantum wells can be developed up to and including 50 Å in thickness. Quantum wells can also be developed with a depth of at least 40 meV.



### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying figures, in which like reference numerals refer to identical or functionally-similar elements throughout the separate views and which are incorporated in and from part of the specification, further illustrate the present invention and, together with the detailed description of the invention, serve to explain the principles of the present invention.

Figure 1 is a graphical illustration of energy v. position and strain for a VCSEL having AlGaAs confinement areas, GaAs barrier layers and InGaAs quantum wells;

Figure 2 is a graphical illustration of "energy v. position" and "strain" for a VCSEL having AlGaAs confinement layers, GaAs barrier layers and InGaAsN quantum wells;

Figure 3 is a graphical illustration of "energy v. position" and "strain" for a VCSEL having GaAsN barrier layers and InGaAsN quantum wells;

Figure 4 is a graphical illustration of "energy v. position" and "strain" for a VCSEL having AlGaAs confinement layers, GaAsN barrier layers and InGaAsN quantum wells;

Figure 5 is a graphical illustration of "energy v. position" and "strain" for a VCSEL having GaAsN barrier layers and InGaAsNSb quantum wells;

Figure 6 is a graphical illustration of "energy v. position" and "strain" for a VCSEL having GaAs barrier layers and GaInAsNSb quantum wells;

Figure 7 is a graphical illustration of “energy v. position” and “strain” for a VCSEL having AlGaAs barrier layers and InGaAsN quantum wells;

5 Figure 8 is a graphical illustration of “energy v. position” and “strain” for a VCSEL having GaAs barrier layers and GaAsNSb quantum wells with >1% nitrogen;

10 Figure 9 is a graphical illustration of “energy v. position” and “strain” for a VCSEL having AlGaAs confinement layers, GaAsN barrier layers and InGaAs quantum wells;

15 Figure 10 is a graphical illustration of “energy v. position” and “strain” for a VCSEL having GaAsN barrier layers and GaAsNSb quantum wells;

20 Figure 11 is a graphical illustration of “energy v. position” and “strain” for a VCSEL having AlGaAs confinement layers, GaAsP barrier layers and GaAsSbN quantum wells;

25 Figure 12 is an exemplary sectional view of a VCSEL in accordance with an embodiment of the present invention;

Figure 13 is another exemplary sectional view of a VCSEL in accordance with another embodiment of the present invention;

30 Figure 14 is a graphical illustration of “energy v. position” for a VCSEL having three quantum wells with depths of ~125 meV for valence bands and ~250 meV for conduction bands;

Figure 15 is a graphical illustration of “energy v. position” for the VCSEL of FIG. 14 wherein recombination within the quantum wells is shown;

Figure 16 is a graphical illustration of "energy v. position" for the VCSEL of FIG. 14 wherein total power within the quantum wells is shown;

5        Figure 17 is a graphical illustration of "energy v. position" for a VCSEL having three quantum wells with depths of ~60 meV for valence bands and ~120 meV for conduction bands;

10        Figure 18 is a graphical illustration of "energy v. position" for the VCSEL of FIG. 17 wherein recombination within the quantum wells is shown;

15        Figure 19 is a graphical illustration of "energy v. position" for the VCSEL of FIG. 17 wherein total power within the quantum wells is shown;

20        Figure 20 is a graphical illustration of "energy v. position" for a VCSEL having three quantum wells with depths of ~40 meV for valence bands and ~80 meV for conduction bands;

      Figure 21 is a graphical illustration of "energy v. position" for the VCSEL of FIG. 21 wherein recombination within the quantum wells is shown; and

      Figure 22 is a graphical illustration of "energy v. position" for the VCSEL of FIG. 21 wherein total power within the quantum wells is shown.

## DETAILED DESCRIPTION OF THE INVENTION

The novel features of the present invention will become apparent to those of skill in the art upon examination of the following detailed description of the invention or can be learned by practice of the present invention. It should be understood, however, that the detailed description of the invention and the specific examples presented, while indicating certain embodiments of the present invention, are provided for illustration purposes only because various changes and modifications within the scope of the invention will become apparent to those of skill in the art from the detailed description of the invention and claims that follow.

Making long wavelength quantum wells on GaAs has proven to be very difficult, but technology presented in this the following description has advanced to the point that longer wavelength quantum wells and higher efficiency VCSELs are now feasible. One issue is that long wavelength compounds tend to not be lattice matched to GaAs. This has been alleviated recently using nitrogen in the quantum wells, which reduces the energy band and reduces the lattice constant in contrast to every other band gap reducing element, thus allowing the inclusion of other elements (e.g., In, Sb), and which reduces the band gap but increases the lattice constant. Unfortunately, the use of nitrogen can have the negative aspect of reducing confinement in the valence band and may tend to make poorer utility material as more nitrogen is added.

This invention can use strain compensation with or without nitrogen in the barrier layers to allow more indium and/or Sb incorporation in the quantum wells without relaxation and thus achieve longer wavelengths. A trade off of the effects on well depth of the Sb and N can also be accomplished so that conduction band wells of at least 0.07 eV and valence band wells of at least 0.05 eV are achievable.

A preliminary description to Figures 1-11 will now be provided prior to describing the benefits of the invention in detail. Referring to Figure 1, portions of the illustrations in Figure 1-11 on the left hand-side of the drawings are meant to graphically represent the position of a quantum well 11, barrier layers 12, and confinement layers 13 of a VCSEL. Power is represented by drawing lines made vertically with respect to the position of the components mentioned. On the right hand of Figures 1-11, strain for each illustrated device is also shown graphically, with compression also being represented vertically downwards and tension represented vertically upwards.

Referring to Figure 1, a graphical illustration of "energy v. position" and "strain" for a VCSEL having AlGaAs confinement layers 13, GaAs barrier layers 12 and an InGaAs quantum well 11 is shown and will serve as a benchmark for adjustments made in Figures 2-11. With use of a InGaAs quantum well on a GaAs substrate, longer wavelengths can be achieved, however, strain is also caused in the quantum well as shown by the depth 15 of the associated strain measurement.

Referring to Figure 2, a VCSEL is shown having AlGaAs confinement layers, GaAs barrier layers and a InGaAsN quantum well. Nitrogen is added to the InGaAs quantum well of Figure 1, which resulted in a decrease in energy and valence band confinement. Here in Figure 2, however, strain was reduced when compared to the nitrogen-free device of Figure 1.

25

Referring to Figure 3, nitrogen (N) is also added to the barrier layers of the device shown in Figure 2. As shown by the arrows 31 in Figure 3, the hole well is recreated with the introduction of nitrogen in the barrier layers. In addition, strain compensation 33 was provided to the device with the addition of

nitrogen to the barrier layers. It should be noted that strain compensation would be realized even where nitrogen is not also introduced in the quantum well.

Referring to Figure 4, aluminum (Al) is now added to the confinement layers/areas of the device shown in Figure 3. Providing Al to the confinement layers eliminates or substantially reduces undesirable wells at the edges of the device as shown by the arrows 41 in the figure. The introduction of aluminum, however, has a negligible effect on the devices strain.

Referring to Figure 5, antimony (Sb) is now added to the quantum well of the device previously viewed in Figure 4. The introduction of Sb to the quantum well causes a decrease in the band gap, an increase in the valence band well, and a decrease in the conduction band well. Strain in the device is increased with the introduction of Sb.

Referring to Figure 6, antimony (Sb) was added to the quantum well for the device illustrated in Figure 2. The band gap for the device increases the valence band well 61, but decreases the conduction band well 62. Compressive strain in the quantum well is also shown to increase with Sb.

Referring to Figure 7, aluminum (Al) is added to the barrier and confining layers of the device first shown in Figure 2. As seen in the graphical illustration, the valence band well is recreated using Al. Strain compensation is unremarkable from its initial position in Figure 2.

Referring to Figure 8, a Indium free device is shown. Indium is removed from the device shown graphed in Figure 6. The quantum well includes GaAsNSb. Device strain is shown to improve with the removal of In.

Referring to Figure 9, nitrogen is shown to be removed from the quantum well for the device shown in Figure 4. The removal of N from the quantum well increases band gap and hole confinement. Strain, however, is also increased in the quantum well, but is compensated for in the barrier region.

5

Referring to Figure 10, a strain compensated device is illustrated. The device of Figure 8 is improved by adding nitrogen to the barrier layers and aluminum to the confining layers. The quantum well is GaAsSbN. This combination increases the hole well and decreases the electron well. The overall strain in the device is reduced.

10

Referring to Figure 11, additional strain compensation is shown by adding phosphorous (P) to the barrier layers. The device in Figure 11 is shown to have AlGaAs confinement layers, and a GaAsSbN quantum well. Indium can also be used in the quantum well.

15

By normal means it is impossible to reach 1310 nm quantum wells used in datacom VCSELs and edge emitters. Referring to Figure 1, what is illustrated is a typical InGaAs strained quantum well on GaAs. By using nitrogen for strain compensation in the barriers (fig. 4, 9), enough indium can be added to the quantum wells without relaxation to reach 1310 nm, and because little or no nitrogen is used in the quantum well itself hole confinement and material quality are maintained. Using AlGaAs confining layers with sufficient Al to avoid extra wells being formed is advantageous.

20

25

As mentioned above, Figure 8 shows a GaAsSbN quantum well with GaAs barriers. In this case, both Sb and nitrogen lower the band gap. The Sb causes the quantum well to tend towards poor electron confinement with good hole confinement, and the nitrogen tends to go in the opposite direction towards poor hole confinement and good electron confinement. By adjusting the ratio of

30

these at least 0.07 eV well depth in the conduction band, and 0.05 eV depth in the valence band can be achieved while achieving both 1310 nm and 1550 nm light emission.

5           If large quantities of Sb and little N are used in the quantum wells such that there is excessive compressive strain in the quantum wells, invention aspect 1 can be combined with this to compensate the excessive compressive strain. That is nitrogen or phosphorous can be added to the barriers layers because it tends to deepen the electron well which the Sb in the quantum well  
10           tends to shallow the electron well. It is also useful to increase the gap of the confining layers with Al or even P once again to avoid extra wells.

          Indium can be used in the quantum well of invention to adjust the wavelength, well depths and strain in the quantum wells. As the band gap  
15           shrinks, the wells become more compressive. But adding indium has only a secondary effect on the relative band offsets (valence band or conduction band) as shown in Figures 5 and 6. Fig 6 will work for both 1310 nm and 1550 nm active regions.

20           As shown in figure 7, AlGaAs barrier layers can be used for InGaAsN quantum wells to increase the hole well depth. Because nitrogen increases the electron effective mass the quantum wells containing nitrogen can be made thinner, that is less than 50 Å. In VCSELs, this means there are more quantum wells.

25           All aspects of the present invention can apply to single as well as multiple quantum wells in both edge emitters and VCSELs and other semiconductor lasers. In all of the above, at least a 0.07 eV well depth is maintained in the conduction band, and a 0.05 eV depth is maintained in the valence band.



The lack of steps obtained using 100 or 111 on orientation material makes it easier to grow more highly strained layers without relaxation. Epi flattening techniques, which reduce the bunching of steps, can be used in combination with the above. Intra-quantum well mechanical stabilizers can also  
5 be used with the above.

Referring to Figure 12, illustrated is a sectional view of a vertical cavity surface emitting laser **100** (VCSEL). The VCSEL **100** can be grown by techniques such as metal organic molecular beam epitaxy, or metal-organic  
10 chemical vapor deposition. Reference is made to U.S. Patent No. 5,903,589, assigned to the assignee for the present invention, which describes methods of VCSEL fabrication use in the art. The VCSEL can preferably be grown on a GaAs substrate **101** due to the robust nature and low cost of the material, however it should be recognized that semiconductor materials, Ge for example,  
15 could also be used as the substrate. The VCSEL **100** can then be formed by disposing layers on the substrate.

Epitaxial layers can include: a first mirror stack **105** disposed on the substrate **101**, a first cladding region **108** disposed on the first mirror stack **105**,  
20 an active region **110** disposed on the first cladding region **108**, a second cladding region **112** disposed on the active region **110**, and a second mirror stack **115** disposed on the second cladding region **112**. The active region **110** can further includes one or more quantum wells **120** being separated from each other by barrier layers **125**, depending on the application for which the VCSEL  
25 **100** is designed. One of ordinary skill in the art can find it obvious to differ the number of quantum wells **120** in the VCSEL active region **110**.

The first mirror stack **105** can be grown by epitaxially depositing mirror pair layers **106** on the substrate **101**. In order to crystal lattice match mirror

stack **105** to the substrate **101**, a suitable semiconductor material system for the mirrored pairs **106** should be deposited. In this specific example, which shouldn't be taken as a limitation of the full scope of the present invention, the substrate **101** is GaAs, therefore a GaAs/AlGaAs material system can be employed. To achieve a high percentage of reflectivity, the number of mirror pair layers **106** in the stack **105** can usually range from 20 to 40, depending on the difference between the refractive indices of the layers. Different refractive indexes are also achievable by altering the Aluminum content in the mirror stack **105**.

A first cladding region **108** can be made of one or more layers epitaxially disposed on the first mirror stack **105**. The first cladding region **108** in the currently described embodiment of the invention can be made of a GaAsN material system.

It has been shown that Nitrogen added to the quantum well **120** can have the effect of increasing the strain between the layers, which reduces the band gap energy of the excited state. Band gap energy reduction generally decreases the amount of energy required to excite the material, and increases the wavelength of the emitted photon. This can be desirable to achieve longer wavelength VCSELs **100**. The more Nitrogen that is added to the quantum well **120**, the greater this reduction in band gap energy can be, and thus longer wavelength VCSELs **100** can be produced.

By using nitrogen in the GaAsN barrier layers and secondarily in the quantum wells themselves, the strain in the structure can be reduced, which can increase the allowable thickness of the quantum wells, and the energy gap can be reduced both which can increase the allowable wavelength.

The use of nitrogen in the quantum wells can make the valence band discontinuity nonconfining or type 2. By using AlGaAs or AlGaAsN as the confining material, however, and GaAsN, AlGaAs, or AlGaAsN or GaAsP barrier layers, the nonconfining problem can also be reduced. In addition, if Sb  
5 replaces a portion of the As in the quantum well, the type II transition caused by nitrogen can further be avoided allowing even more nitrogen. Because even more nitrogen is allowable, more indium is also allowable. Because nitrogen, indium, and Sb all reduce the band gap energy, the achievable wavelengths extend to wavelengths longer than either 1310nm used for datacom or 1550 nm  
10 used for telecom.

By adding Nitrogen to the InGaAs quantum wells, the overall strain in the well can become significantly less allowing more indium before reaching the critical thickness, thus making longer wavelength VCSELs possible. Using  
15 nitrogen for strain compensation in the barriers, the allowable strain in the quantum well region can increase meaning even more indium can be used in the quantum wells. More indium is allowable without violating the critical thickness, making for an even lower band gap and longer wavelengths. In addition, using nitrogen in the barrier layers between the quantum wells can  
20 also reduce the energy of these barriers in the conduction band making the energy of the quantum state lower, further increasing the allowable wavelength. Using nitrogen in the barrier layers can also be advantageous in avoiding type II behavior in the valence band because as nitrogen is incorporated in the quantum wells, the conduction band discontinuity increases, and the valence  
25 band discontinuity decreases. In addition, use of AlGaAs or AlGaAsN for the confining structure can further avoid unintentional wells in the valence band at the barrier layer confining layer boundary. Finally, the use of Sb in the quantum well can reduce the band gap energy further, while avoiding the type II behavior (allowing even more nitrogen). All of these aspects contribute to the ability to  
30 create very long wavelength active regions.

Introducing Nitrogen into the active region **110** is not generally without drawbacks. GaN and InN can have large differences in their lattice constants as well as optimal growth conditions. Due to this lattice mismatch, the quality of the material can be greatly compromised when layers comprising the active region **110** are grown beyond a certain critical thickness. Layers thicker than this critical thickness can have misfit dislocations, relaxing the strain between the layers, and decreasing the material quality. This can substantially compromise the quality of the VCSEL **100**.

By including Nitrogen in the barrier layers **125**, the band gap energy decrease can be observed as it is when Nitrogen is added only to the active region **110**. However, the amount of Nitrogen that is needed in the active region **110** to achieve a given band gap energy reduction, and therefore a longer wavelength, can be reduced. The lattice mismatch can therefore not generally be as severe as when Nitrogen is added to the active region **110** alone, thus making the material system easier to fabricate. Higher quality VCSELs can be achieved by introducing Nitrogen into the barrier regions **125** than when Nitrogen is only added to the active region **110**.

Active region **110** can next be epitaxially deposited on the first cladding region **108**. The active region **110** can include one or more quantum wells **120**. The preferred embodiment uses quantum wells **120** of less than 50 angstroms. When Nitrogen is introduced into the active region **110** or the cladding region **108**, **112**, the effective electron mass in the regions can increase dramatically. With this increased density of the states, the amount of Indium or Nitrogen needed to produce a given amount of gain in the active region **110** generally decreases. Therefore, the volume of the quantum well **120** can also be decreased, giving less volume for parasitics to occur in.

A second cladding region **112** can be made of one or more layers epitaxially disposed on the active region **110**. The second cladding region **112** can be made of a GaAsN material system.

5

A second mirror stack **115** can next be grown by epitaxially depositing mirror pairs layers **116** on the second cladding region **115**. In order to crystal lattice match mirror stack **115** to the substrate **101**, a suitable semiconductor material system for the mirrored pairs **116** should be deposited. The substrate **101** is formed of GaAs, therefore a GaAs/AlGaAs material system can be employed. To achieve a high percentage of reflectivity, the number of mirror pair layers **116** in the stack **115** can usually range from 20 to 40, depending on the difference between the refractive indices of the layers. Different refractive indexes are achievable by altering the Aluminum content in the mirror stack **115**.

10  
15

Referring now to Figure 13, an alternate embodiment of the present invention is shown. A flattening layer **235** can be sandwiched between the lower confining layer and the quantum wells. When the various layers are grown on the substrate, bunching of molecular steps form on the surface of the newly formed layers. The steps on the layer's surface increase the likelihood that layers adjacent to the substrate can dislocate from the substrate. A heavily compressively strained InGaAs flattening layer **235** grown before the active region **210** at a distance sufficient to minimize the straining effects on the quantum well layers generally has the effect of flattening the surface to which the active region **210** is disposed. The distance between the flattening layer **235** and the quantum wells can be several hundred angstroms. Growing this flattening layer **235** between the lower confining layer **201** and the first mirror stack **205** flattens out these molecular steps. The surface can be further flattened when the epi layers are grown on "100 or 111 on" orientation

20  
25

substrates. If the substrate is in "off" orientation, the number of molecular steps can increase and the likelihood of bunching of steps increases, thereby increasing the likelihood for dislocation. By flattening the surface that the stacks are deposited on, the strain between layers can be further increased through  
5 the addition of greater amounts of In or Sb in the active region. This increased In or Sb generally decreases the band gap energy, thereby making it easier to grow VCSELs 201 that emit longer wavelengths.

Quantum well depth can be an important consideration in achieving  
10 optimal gain from VCSEL quantum wells. Comprehensive, up-to-date compilations of band parameters useful for the development of semiconductor devices, such as VCSELS, are generally discussed in a paper entitled "Band parameters for III-V compound semiconductors and their alloys," by Vurgaftman, Meyer and Ram-Mohan (Journal of Applied Physics, Volume 89,  
15 Number 11, 1 June 2001). The paper provides some insight for the skilled in the art on calculating band offsets, thereby enabling the achievement of optimal quantum well depth utilizing various materials, and is hereby incorporated by reference into the present disclosure for its teaching.

20 Quantum wells for VCSELs should be designed in order to promote confinement of carriers within the quantum wells instead of outside of the quantum wells, while at the same time not being so deep as to prohibit adequate flow of carriers between the wells. Proper quantum well depth will maximize the gain in the quantum wells of a VCSEL, which minimizes the  
25 threshold current and maximizes slope efficiency (both desirable outcomes). Luminescence and gain within a quantum well is related to the product of holes and electrons within the quantum well. Quantum well depth is established by setting band offsets. Two bands used to determine the quantum well depth are the valence and conduction bands (the valence band associated with hole wells  
30 and the conduction band with electron wells). Setting of the bands determines

the offsets (meV, mili electron volts) for the quantum well and provides depth associated with the confinement of holes and electrons.

Figures 14-22 provide graphical illustrations of VCSEL behavior at different well depths. Although the simulations illustrated in Figures 14-22 were conducted on AlGaAs quantum wells, the overall analysis is applicable to other materials since temperature will generally be the same and effective masses are not vastly different between devices.

Figures 14-16 are a first group of graphs representing the analysis of a normal set of three quantum wells 1401 for an 850 nm VCSEL under bias (actively lasing). In this case there is substantial p-doping, which suppresses the electron concentration relative to the hole concentration. As shown on the vertical axis of the graph in FIG. 14, well depth of three quantum wells 1401 was established by setting the valence band offsets 1405 at approximately 125 meV and the conduction band offset 1410 at 250 meV. It should be appreciated that the quantum well number does not have to be limited to three. As can be seen within the graphical data in FIG. 15, there is little recombination outside the three quantum wells shown. This can be seen where more electrons 1507 and holes 1509 are found recombining within the quantum wells than the area outside (or in-between) the quantum wells where some holes 1511 and minimal electrons exist. Although enough of both carriers are present, thus enabling sufficient transport between the wells. Referring to FIG. 16, the total recombination 1603 of holes with electrons occurring within the wells, rather than outside the wells 1611, results in good luminescence and thus good gain for the VCSEL quantum wells.

Figures 17-19 illustrate a second group of graphs representing the analysis of quantum wells under bias. Referring to FIG. 17, quantum well depths were set at approximately 60 meV for valence bands 1703 and 120 meV

for conduction bands 1705. Referring to FIG. 18, there is shown an increasing number of holes and electrons 1811 outside the three quantum wells. Such loss of holes and electrons outside of the quantum wells results in less luminescence 1901 and, therefore, less gain resulting from the quantum wells as shown in FIG. 19

Figures 20-22 are a third group of graphs representing the analysis of quantum wells under bias. The well depths for the three quantum wells were set at approximately 40 meV for valence bands 2003 and 80 meV for conduction bands 2005. As can be seen in FIG. 21, recombination 2101 outside of the three quantum wells has become quite large. Referring to FIG. 22, loss of recombination within the quantum wells results in a significantly less luminescence 2201 and gain due to undesirable parasitic luminescence 2205.

Based on the foregoing analysis for the quantum wells represented in the three groups, it would be desirable to develop VCSELs having quantum wells hole depths of at least 40 MeV and electron depths of at least 80 MeV. Such a setting for the valence and conduction bands would provide at least minimally acceptable gain; however, optimal quantum well hole well depths have been shown to be up to and including 125 MeV for the Valence bands and conduction bands with a setting of up to and including 250 MeV. Well depths even greater may be acceptable, as long as sufficient transport between the wells is maintained by thermionic emission, tunneling, or both.

The embodiment and examples set forth herein are presented to best explain the present invention and its practical application and to thereby enable those skilled in the art to make and utilize the invention. Those skilled in the art, however, will recognize that the foregoing description and examples have been presented for the purpose of illustration and example only. Other variations and modifications of the present invention will be apparent to those of skill in the art,



and it is the intent of the appended claims that such variations and modifications be covered. The description as set forth is not intended to be exhaustive or to limit the scope of the invention. Many modifications and variations are possible in light of the above teaching without departing from the spirit and scope of the following claims. It is contemplated that the use of the present invention can involve components having different characteristics. It is intended that the scope of the present invention be defined by the claims appended hereto, giving full cognizance to equivalents in all respects.